

# KingProof<sup>®</sup> Primer A

Acrylic primer for KingProof A200.

## DESCRIPTION

KingProof Primer A is an acrylic base coating for use in conjunction with KingProof A200.

## APPLICATIONS

- For use as a primer coat for KingProof A200 top coat.

## ADVANTAGES

- Single component.
- Promote adhesion between concrete substrate and subsequent KingProof A200 layers.

## METHOD OF USE

### Surface Preparation

Surfaces to receive KingProof Primer A should be clean, sound, and free from oil, grease, dirt and loose particles. Substrate should be dry, with no standing water. Spalled surfaces, cracks and defected concrete should be repaired. New concrete substrate should be at least 14 days old.

### Application

KingProof Primer A can be applied by brush, roll, or airless spray machine. One coat should be applied at the rate of 5 m<sup>2</sup> per liter and allowed to dry before applying the first coat of KingProof A200.

## CLEANING

All tools should be washed and cleaned immediately after use with clean water.

## PACKAGING

KingProof Primer A is available in 5 and 25 litres packs.

## COVERAGE

4 - 5 m<sup>2</sup> per litre.

## TECHNICAL PROPERTIES

Colour:	White liquid
Solid content:	45 ± 5%
Specific gravity:	1.0 ± 0.02

## STORAGE

Shelf life is 1 year when stored under cover, out of direct sunlight and protected from extremes of temperature. Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging. For specific storage advice consult KingKrete's Technical Services Department.

## HEALTH AND SAFETY

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs. Treat splashes to eyes and skin immediately. If accidentally ingested, seek medical attention. Reseal containers after use. Use in well ventilated areas and avoid inhalation.



# KingProof<sup>®</sup> Primer A

## NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local KingKrete representative. KingKrete Inc. reserves the right to have the true cause of any difficulty determined by accepted test methods.

## QUALITY AND CARE

All products originating from KingKrete's manufacturing facilities are manufactured under a management system independently certified to conform to the requirements of the quality standard ISO 9001.

\* Properties listed are based on laboratory-controlled tests.

® = Registered trademark of the KingKrete-Group in many countries.

## K KK-ME-03.1-PF-PrimerA-R3-2601

### STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this KingKrete Inc. publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

### NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by KingKrete Inc. either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not KingKrete Inc. are responsible for carrying out procedures appropriate to a specific application.

