

# KingMix<sup>®</sup> 505ES

Premium quality plasticising admixture for concrete masonry products.

## DESCRIPTION

KingMix 505ES is a chloride free, premium quality high range water reducing admixture with air entraining properties based on polycarboxylic polymers with selective additives which are especially formulated for factory-line concrete production such as concrete blocks and bricks.

KingMix 505ES can significantly assist in the production of a more uniform and consistent quality mixes in factory-line concrete products, it can be also used for light weight concrete production.

## APPLICATIONS

KingMix 505ES can be successfully used in the following applications:

- ☐ Concrete blocks and bricks.
- ☐ Dry cast concrete.
- ☐ Concrete roofing tiles.
- ☐ Concrete pipes.

## ADVANTAGES

- ☐ Improves the cohesion of the concrete mix.
- ☐ Improves compressive strength.
- ☐ Optimized mix design.

## COMPATIBILITY

KingMix 505ES can be used with all types of Portland cement and cement replacement materials. KingMix 505ES should not be used in conjunction with other admixtures unless KINGKRETE technical department approval is obtained.

## STANDARDS

KingMix 505ES complies with ASTM C494 Type, A and F, depending on dosage used.

## METHOD OF USE

KingMix 505ES should be added to the concrete with the mixing water to achieve optimum performance.

An automatic dispenser should be used to dispense the correct quantity of KingMix 505ES to the concrete mix.

## TECHNICAL PROPERTIES @ 25°C:

|                   |                     |
|-------------------|---------------------|
| Colour:           | Light yellow liquid |
| Freezing point:   | ≈ -5°C              |
| Specific gravity: | 1.04 ± 0.02         |
| Chloride content: | Nil                 |

## DOSAGE

The guidance dosage of KingMix 505ES is 0.4 - 4.0 litre per 100 kg of cementitious materials in the mix, including GGBFS, PFA or micro-silica.

Trials should be conducted to determine the optimum dosage of KingMix 505ES to meet the performance requirements by using the materials and conditions in actual use.

## EFFECTS OF OVER DOSAGE

Over dosing of KingMix 505ES will cause the following:

- ☐ Significant increase in retardation.
- ☐ Significant increase in air content.

Ultimate concrete strength will not be adversely affected and will generally be increased provided that proper concrete curing is maintained.

## CLEANING

KingMix 505ES can be washed with fresh cold water.

## PACKAGING

KingMix 505ES is available in 25 litre jerrycan, 210 litre drums and 1000 litre bulks supply.

## STORAGE

Shelf life is 1 year when stored under cover, out of direct sunlight and protected from extremes of temperature.

Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging. For specific storage advice consult KingKrete's Technical Services Department.

## HEALTH AND SAFETY



# KingMix<sup>®</sup> 505ES

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs. Treat splashes to eyes and skin immediately. If accidentally ingested, seek medical attention. Reseal containers after use. Use in well ventilated areas and avoid inhalation

## NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local KingKrete representative. KingKrete Inc. reserves the right to have the true cause of any difficulty determined by accepted test methods.

## QUALITY AND CARE

All products originating from KingKrete's

manufacturing facilities are manufactured under a management system independently certified to conform to the requirements of the quality standard ISO 9001.

\* Properties listed are based on laboratory-controlled tests.

® = Registered trademark of the KingKrete-Group in many countries.

K KK-NA-01.5-MX-505ES-R3-2601

### STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this KingKrete Inc. publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

### NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by KingKrete Inc. either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not KingKrete Inc. are responsible for carrying out procedures appropriate to a specific application.

KingKrete North America  
www.kingkrete.com

**Disclaimer:** the IAS mark relates to certified management system and not to the product mentioned on this datasheet

