

KingProof[®] Tape BB

Waterproof polythene coated cloth tape.

DESCRIPTION

KingProof Tape BB is a waterproof polythene coated cloth tape with a rubber-based pressure sensitive adhesive.

APPLICATIONS

For use as a bond breaker in conjunction with the KingSeal range of sealants where the joint depth available is inadequate to accommodate a foam polyethylene joint backing.

METHOD OF USE

Joint Preparation

All surfaces must be clean, dry and grease free. KingProof Tape BB is supplied in roll form and the tape can be applied to the back of the joint without stretching.

PACKAGING

KingProof Tape BB is available in roll form.

AVAILABLE SIZES

50 m x 4.5, 50 m x 6 mm, 50 m x 10 mm, 50 m x 12 mm.

THICKNESS

0.20 mm.

ACCESSORIES

- ☐ King Cleaner TB130: 1 liter tin (Toluene based – not suitable for use with plastics or delicate finishes).
- ☐ King Cleaner AB160 : 1 liter tin (Alcohol based).

TECHNICAL PROPERTIES

Colour:	Black
Adhesion:	4.0 N/cm
Tensile strength:	35.0 N/cm
Temperature resistance:	Up to 60°C
Adhesion to backing (unwind):	3.0 N/cm

STORAGE

Shelf life is 1 year when stored under cover, out of direct sunlight and protected from extremes of temperature.

Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging. For specific storage advice consult KingKrete's Technical Services Department.

HEALTH AND SAFETY

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs. Treat splashes to eyes and skin immediately. If accidentally ingested, seek medical attention. Reseal containers after use. Use in well ventilated areas and avoid inhalation.

NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local KingKrete representative.

KingKrete Inc. reserves the right to have the true cause of any difficulty determined by accepted test methods.

QUALITY AND CARE



KingProof[®] Tape BB

All products originating from KingKrete's manufacturing facilities are manufactured under a management system independently certified to conform to the requirements of the quality standard ISO 9001.

* Properties listed are based on laboratory-controlled tests.

® = Registered trademark of the KingKrete-Group in many countries.

R3-2601

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this KingKrete Inc. publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by KingKrete Inc. either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not KingKrete Inc. are responsible for carrying out procedures appropriate to a specific application.

KingKrete North America
www.kingkrete.com

Disclaimer: the IAS mark relates to certified management system and not to the product mentioned on this datasheet

