

KingProof[®] B100

Water based rubberized bitumen protective coating.

DESCRIPTION

KingProof B100 is black/brown emulsified bitumen liquid reinforced with rubber, acting as damp-proof, vapour barrier and protective coating for concrete and masonry.

APPLICATIONS

KingProof B100 provides a protective coating and vapour barrier for the following:

- ☐ Underground concrete foundations.
- ☐ Concrete and masonry block walls.
- ☐ Walls below cladding systems.

ADVANTAGES

- ☐ Resists attack by chloride and sulphate ions present in ground water.
- ☐ Applied by brush which makes it easy to use.
- ☐ Economical.
- ☐ Water base has no solvents.
- ☐ Asbestos free.
- ☐ Does not rot.

STANDARDS

KingProof B100 complies with ASTM C309-93 when applied with two coats at a rate of 2 m²/litre per coat.

METHOD OF USE

Surface Preparation

Surface preparation is very important to get the highest performance of KingProof B100. Any surface to be coated must be clean, sound and free of oil or grease. Any oil or grease contamination should be removed with a chemical degreaser. All holes should be filled with a suitable cementitious mortar before application of KingProof B100.

Primer Coat

There is generally no need for primer coat. Dusty surfaces should be primed with a coat of KingProof B100, diluted with an equal quantity of cool, clean water and allowed to dry.

TECHNICAL PROPERTIES @ 25°C

Form	Liquid
Density	1.05 ± 0.02 g/cm ³
Over coating time	10 hr
Application temperature	5 - 45°C
Drying time:	3 - 5 hr
VOC	< 40 gr/ ltr

APPLICATION

It is recommended that two coats of KingProof B100 be applied. The second coat should be applied at a right angle to the first coat. Allow a minimum of 3 hours between coats. Stir well before use. KingProof B100 may be applied by brush, broom or squeegee.

COVERAGE

3 - 5 m²/litre, depending on surface roughness.

CLEANING

Tools and equipment can be cleaned with water when still wet.

Dried KingProof B100 may be removed with KINGKRETE Solvent.

PACKAGING

KingProof B100 is available in 18 and 200 litre drums.

STORAGE

Shelf life is 1 year when stored under cover, out of direct sunlight and protected from extremes of temperature.

Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging. For specific storage advice consult KingKrete's Technical Services Department.

HEALTH AND SAFETY

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs. Treat splashes to eyes and skin immediately. If accidentally ingested, seek medical attention. Reseal containers after use. Use in well ventilated areas and avoid inhalation.

NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information



KingProof® B100

contact your local KingKrete representative.

KingKrete Inc. reserves the right to have the true cause of any difficulty determined by accepted test methods.

All products originating from KingKrete's manufacturing facilities are manufactured under a management system independently certified to conform to the requirements of the quality standard ISO 9001.

* Properties listed are based on laboratory-controlled tests.

® = Registered trademark of the KingKrete-Group in many countries.

QUALITY AND CARE

KK-SA-03.1-PF-B100-R3-2601

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this KingKrete Inc. publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by KingKrete Inc. either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not KingKrete Inc. are responsible for carrying out procedures appropriate to a specific application.

KingKrete South America
www.kingkrete.com

Disclaimer: the IAS mark relates to certified management system and not to the product mentioned on this datasheet





KingProof[®] B100
