

KingCoat[®] Primer S

Silane/siloxane based hydrophobic primer.

DESCRIPTION

KingCoat Primer S is a penetrating hydrophobic silane/siloxane based primer. It is used as a primer for KingCoat S acrylic based protective coating. When applied, it reacts with concrete and masonry surfaces producing a clear hydrophobic barrier that prevents the passage of water and hence protects exposed reinforced concrete structures from attack by chloride ions.

APPLICATIONS

- Deep penetration into substrate.
- Very good reduction of water and chloride intrusion.
- Breathable, allows for water vapour release.

ADVANTAGES

- Highly durable and tough wearing marking paint.
- Quick drying easy to apply (one component).
- High opacity and available in different colours.
- Excellent adhesion to all types of new (28 days) and old concrete.

METHOD OF USE

Surface Preparation

Surface must be clean, sound and free from oil, grease, curing compound, or any contamination. Any contaminants should be removed by light grit blasting.

Surfaces containing slight surface imperfection or blowholes should be filled with a skim coat of cementitious repair mortar such as KingRep S, Deep holes and defected areas should be repaired with cementitious products from KINGKRETE-Repair range.

Application

KingCoat Primer S should be spray or brush applied at the rate of 0.2 litre per square meter.

KingCoat Primer S should be left to cure for 5 hours at 25°C before the application of KingCoat S.

Specific gravity:	0.85 ± 0.02
VOC: ASTM D2369	< 750 g/ltr

CLEANING

Tools and equipment can be cleaned with KINGKRETE-solvent when wet. Hardened materials must be cleaned mechanically.

PACKAGING

KingCoat Primer S is available in 18 and 200 litre drums.

COVERAGE

0.2 litre/m² per coat.

STORAGE

Shelf life is 1 year when stored under cover, out of direct sunlight and protected from extremes of temperature. Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging. For specific storage advice consult KingKrete's Technical Services Department.

HEALTH AND SAFETY

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs. Treat splashes to eyes and skin immediately. If accidentally ingested, seek medical attention. Reseal containers after use. Use in well ventilated areas and avoid inhalation.



KingCoat[®] Primer S

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local KingKrete representative. KingKrete Inc. reserves the right to have the true cause of any difficulty determined by accepted test methods.

QUALITY AND CARE

All products originating from KingKrete's manufacturing facilities are manufactured under a management system independently certified to conform to the requirements of the quality standard ISO 9001.

* Properties listed are based on laboratory-controlled tests.

® = Registered trademark of the KingKrete-Group in many countries.

KKK-SAS-04.2-CT-PrimerS-R3-2601

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this KingKrete Inc. publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by KingKrete Inc. either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not KingKrete Inc. are responsible for carrying out procedures appropriate to a specific application.

