

KingInsulate® PF50

A flexible PVC waterproofing membrane for underground structures and tunnels.

DESCRIPTION

KingInsulate PF50 is a one part fire rated expanding Polyurethane Foam tested in horizontal and vertical applications to BS476 Part 20. Product is supplied in HCFC and CFC aerosol cans. Material can expand up to 40 times its original volume after application.

APPLICATIONS

- ☒ Sealing joints where fire integrity and insulation is required e.g. walls, floors and partitioning.
- ☒ Perimeter joints around door and window frames and service penetrations.

Note: Not recommended for totally enclosed applications.

STANDARDS

- ☒ Tested to BS476 Part 20- Warrington Report 117611.
- ☒ DIN 4102 Class B2.

PACKAGING

- ☒ KingInsulate PF50 is supplied in 2 different 750ml cans.
- ☒ PF100 G – Gun grade 9 requires foam Applicator Gun.
- ☒ PF100 H – Hand grade (supplied with own nozzle).

STORAGE

Shelf life is 1 year when stored under cover, out of direct sunlight and protected from extremes of temperature.

Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging. For specific storage advice consult KingKrete's Technical Services Department.

TECHNICAL PROPERTIES

Skin time @ 200C/65 % RH:	20 mins.
Trimming time @ 200C/65 % RH:	4 hrs. (deep applications will require longer)
Application temperature:	5 - 300C
Service temperature:	- 20 - 900C

COVERAGE

Joint Size (mm)	Meters per Liter
10 x 10	10.0m
13 x 13	5.91m
15 x 15	4.44m
20 x 10	5.0m
20 x 20	2.5m
25 x 12	3.33m
25 x 25	1.60m
30 x 15	2.22m
30 x 30	1.11m

ACCESSORIES

Cleaners

- ☒ King Cleaner No.17- 1 Litre Tin (Xylene based – not suitable for use with plastics or delicate finishes)
- ☒ King Cleaner No. 16 - 1 Litre Tin (Alcohol Based)

Ancillary Equipment

- ☒ Foam Gun for AR240G

HEALTH AND SAFETY

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs. Treat splashes to eyes

and skin immediately. If accidentally ingested, seek

medical attention. Reseal containers after use. Use in well ventilated areas and avoid inhalation.

NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local KingKrete representative. KingKrete Inc. reserves the right to have the true cause of any difficulty determined by accepted test methods.



KingInsulate® PF50

A flexible PVC waterproofing membrane for underground structures and tunnels.

QUALITY AND CARE

All products originating from KingKrete's Middle East facility are manufactured under a management system independently certified to conform to the requirements of the quality standards ISO 9001, ISO 14001 and ISO 45001.

* Properties listed are based on laboratory-controlled tests.

® = Registered trademark of the KingKrete-Group in many countries.

Ref: KK-10047-MEA-R01 | Issue: 01.2026

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this KingKrete Inc. publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by KingKrete Inc. either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not KingKrete Inc. are responsible for carrying out procedures appropriate to a specific application.

KingKrete Middle East
Qatar – Syria
www.kingkrete.com

Disclaimer: the IAS mark relates to certified management system and not to the product mentioned on this datasheet

